

Top-line door panels form the most exclusive line of the group. Top-line panels are produced in full version or with glass elements placed in panel with a help of aluminum frames. We use aluminum frames and cut patterns, which enables us to use thicker aluminum sheets. This provides more reinforcement and protection from burglary.





PARAMETERS:

- standard dimensions: 1000 x 2000 x 24/36/44 mm,

- available thickness: 24, 36 oraz 44 mm,

- construction: 2,0/20/2,0

2,0 mm milled aluminium plate

20,00 mm rigid polystyrene foam

2,0 mm milled aluminium plate.



DOORS PRESENTED FROM THE OUTSIDE

TL/F 3-S



TL/F 4-S



TL/K 7



TL/K 7-S



TL/MC 1



TL/MC 1-S



TL/MC 2



TL/MC 2-S



TL/MC 4



TL/MC 4-S



TL/MC 5



TL/MC 5-S



DOORS PRESENTED FROM THE OUTSIDE

TL/DW 1



TL/DW 4



TL/DW 1-S





TL/DW 7



TL/DW 7-S



TL/DW 3



TL/DW 5




TL/F 1



TL/DW 3-S



TL/DW 5-S



TL/F 1-S



DOORS PRESENTED FROM THE OUTSIDE

TL/P 10















The entire range of RAL colours. Paint manufacturer may be cohosen according to customers needs.

